

Wooster Products Inc.

Acrylic Safe-Stride Anti-Slip Coating

Application Instructions

Safe-Stride coatings have been formulated for use on concrete, wood and primed metal surfaces. When used properly, Safe-Stride products provide a tough, abrasive, anti-slip coating for walkways, steps, ramps, boat decks, locker room floors, and a variety of other uses.

SURFACE PREPARATION: To insure proper adhesion, all surfaces must be clean and free of dirt, grease, wax, mildew, rust, oil, chalk, and other foreign matter. Spalling or powdery concrete must be repaired to a sound surface before coating. Concrete that is shiny smooth or suspected of treatment with chemical "de-icers" should be etched with diluted muriatic acid to promote bonding. Scuff sanding of glossy painted surfaces is recommended to secure the maximum adhesion of this product.

CEMENT and MASONRY: New concrete should age for at least thirty days prior to being topcoated. Bare and previously painted surfaces merely require preparation as described above before applying one or more coats of Acrylic Safe-Stride.

WOOD: Bare or previously painted wood should be prepared as described above by removing any foreign matter, loose paint, or chalk, and scuff sanding painted glossy areas. Wolmanize-treated wood must be aged a minimum of one year in order for product to adhere. One or two coats of Acrylic Safe-Stride may be applied. Wood priming is not necessary when this product is used properly.

METAL: Any bare metal should be primed with any standard rust inhibiting metal primer following label directions before applying Acrylic Safe-Stride.

APPLICATION: Stir thoroughly upon opening and remix periodically. Apply by brush, roller or trowel at a spreading rate of 100 to 125 sq. ft. per gallon. Thinning of this product is not recommended. When rolling, back brushing immediately after roller application is recommended for uniformity of the surface and durability of the product. Acrylic Safe Stride is dry to walk on or recoat in 18 to 24 hours under normal drying conditions. The maximum hardness of this product is typically achieved in 7 to 14 days. All equipment should be cleaned immediately after use with soap and water and dried for storage.

GENERAL: Acrylic Safe-Stride anti-slip coatings are designed to reduce the hazards of slippery areas -not prevent these hazards.

Do not paint if temperature will be below 50°F within twenty-four hours of application, or if rain is imminent. Do not paint in direct sunlight. This product is not recommended on garage floors on which cars will be parked or for underwater application such as swimming pools. Cool or high temperatures will extend the drying time of this product. This product contains water. Protect from freezing.

IMPORTANT NOTICE TO PURCHASER: THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE: Purchase or use of this product constitutes an agreement with Seller and Manufacturer that, if the product proves to be defective or in any way unsuitable, Seller's and Manufacturer's limit of liability for all damages, including but not limited to incidental or consequential damages, and User's or Purchaser's exclusive remedy, regardless of legal theory, including theories of breach of warranty, negligence and strict liability, shall be to receive, at Seller's or Manufacturer's option, repair of the defective product, an equivalent quantity of replacement product or a refund of the purchase price.



WOOSTER PRODUCTS INC, 1000 SPRUCE ST., WOOSTER, OH 44691

Toll Free: 800-321-4936 Phone: 330-264-2844 Fax: 330-262-4151

Web Site: <http://www.wooster-products.com>

E-mail: sales@wooster-products.com